TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8196)

Marked a fir, 10" dia., S14 on E and S15 ¼ S on W faces, for ¼ sec. cor. from which
A Fir, 8" dia., bears S.55°E., 22 lks., mkd: S14 ¼ S BT.
A W.Fir, 8" dia., bears S.65°W., 8 lks., mkd: S15 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones, C. Stone & J. Brady - Feb/March 1967 - C.S. File 54/32-8

Found - 10" corner tree, now 5' fir stob, opened for scribe "S", other "¼ 14" visible on east face. West face rotten.
8" D.Fir now rotten stump, S.55°E., 14.5 ft.
No trace of SW BT.
Set - Brass cap on E side of corner stob mkd: T31S R9W
COUNTY SURVEYOR ¼ S 15|S 14
OFFICE 1967
New BTs- 7" D.Fir S.12°W., 18.7 ft. mkd: ¼ S15 CS BT.
5" D.Fir N.28½°E., 14.4 ft. mkd: ¼ S14 CS BT.

Tony Hostetter - For: Roseburg Resources Co. & Plum Creek - Sept. 2009 - M160-4

Found - 1967 Brass cap as described by Douglas Co. Surveyor (C.S. file 54/32) from which
10" Fir, corner tree, scribing visible bears North 0.7 ft.
7" Fir, now 14", S.12°W., 18.7 ft.
5" Fir, now 12", N.28½°E., 14.4 ft.
New BTs- 12" Fir, scribed "S14 ¼ BT" bears N.89°E., 13.9 ft. to spike.
10" Fir, scribed "S15 ¼ BT" bears S.79°W., 20.8 ft. to spike.
5" Fir, scribed "S15 ¼ BT" bears N.18°W., 25.4 ft. to spike.