TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8198)

Marked a fir, 6" dia., S11 on E & S10 ¼ S on W faces for the ¼ sec. cor. from which
A fir, 10" dia., bears S.20°E., 17 lks., mkd: S11 ¼ S BT.
A W.Fir, 10" dia., bears S.85°W., 8 lks., mkd: S10 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Feb./March 1967 - C.S. File 54/32-10

Found - Orig. 6" corner tree, now down, scribing visible "S10 ¼S"
10" D.Fir now down, S.20°E. 11.2 ft shows good scar.
10" W.Fir now down, S.85°W., 5.3 ft. scribe visible, stump show "BT" log "¼S"
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T31S R9W
OFFICE 1967 ¼ S 10|S 11
New BTs- 24" D.Fir S.19°E., 55.3 ft., mkd: ¼ S11 CS BT.
20" D.Fir N.71°W., 94.9 ft., mkd: ¼ S10 CS BT.

Carl Sweeden - For: Superior Lumber Co - Jan. 2003 - M 141-39

Found - 2½" BC up 0.70'
20" D.Fir BT now down, N.71°W., 94.9' to root hole, scribe vis. I tag
22" D.Fir stump 3.6' tall, S.19°E., 55.3', metal cap, no bark, scar vis., tag
New - 8" D.Fir BT, S.52°E., 7.85' scribed "W¼ S11 BT" & tag
7" D.Fir BT, S.88°E., 5.0', scribed "W¼ S11 BT" & tag
6" D.Fir BT, S.88°W., 7.0', scribed "E¼ S10 BT" & tag
Steel posts 1.0' West of BC.