

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T30-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7381)

-----

Marked a Cedar 6" dia., for cor. of secs. 34, 35, 2 and 3, from which

A Fir 10" dia., bears N.52°W., 16 lks. dist.

A Fir 6" dia., bears S.30°E., 25 lks. dist.

A Hemlock 6" dia., bears S.5°W., 16 lks. dist.

A Cedar 5" dia., bears N.65°E., 14 lks. dist.

Fd. and Used in GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7403)

Survey by Romanso E. Ware - For: Roseburg Lumber Co. - Jan. 1980 - M 79-18

-----

Set chisled "X" in rock, from which

12" Fir bears N.28°E., 43.2 ft. scribed T30S R9W S35 BT.

36" Cedar bears N.40°W., 28.2 ft. scribed T30S R9W S34 BT

12" Hemlock bears S.16°E., 25.7 ft. scribed T30S R9W S2 BT

20" Cedar bears S.56°W., 54.3 ft. scribed T30S R9W S3 BT.

(No original evidence found)