

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8196)  
-----  
Set a cedar post, 4 ft. long, 4" sq., 24" in the ground, mkd S14 1/4 S on N and S23 on S faces for 1/4 sec. cor. from which  
A cedar, 8" dia., bears S.22°W., 28 lks., mkd: S23 1/4 S BT.  
A cedar, 12" dia., bears N.5°W., 8 lks., mkd: S14 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones, C. Stone & J. Brady - Feb/March 1967 - C.S. File 54/32-14  
-----  
Found - Orig. 12" now 17" cedar N.5°W., 5.3 ft. opened for scribe "1/4"  
No trace of SW Cedar  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T31S R9W  
OFFICE 1/4 S 14  
1967 S 23  
New BT - 13" W.Fir S.79°W., 98.3 ft. mkd: 1/4 S23 CS BT.

Tony Hostetter - For: Roseburg Resources Co. & Plum Creek - Sept. 2009 - M160-4  
-----  
Found - 1967 Brass cap and accessories described by Douglas Co. Surveyor (C.S. file 54/32)  
New BTs- 6" Madrone, scribed "S14 1/4 BT" bears N.71°52'E., 0.46 ft. to spike  
15" Fir, scribed "S23 1/4 BT" bears S.14°19'E., 25.12 ft. to spike.  
18" Cedar, scribed "S15 1/4 BT" bears S.29°49'W., 47.0 ft. to spike.