TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8198)

Set a basalt stone 16x12x5", 12" in the ground, mkd. ¼ on N face for ¼ sec. cor. from which
A fir, 30" dia., bears N.25°E., 8 lks., mkd: S11 ¼ S BT.
A fir, 16" dia., bears S.30°E., 26 lks., mkd: S14 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Cliff Stone - Feb. 1967 - C.S. File 54/32-92

Found - Part of Stone at Corner.
16", now 22" D.Fir, S.30°E. 17.2 ft., opened for scribing.
30", now 36 D.Fir, N.25°E. 5.3 ft., shows good scars.
Set - Brass Cap at ¼ Cor. mkd County Surveyors Office 1967 ¼ S 11 / S 14
New BTs- 7" Cedar S.22°E., 43.5 ft. mkd. ¼ S14 CS BT.
10" Cedar N.34°E., 14.3 ft. mkd. ¼ S11 CS BT.

Tony Hostetter - For: Roseburg Resources Co. & Plum Creek - Sept. 2009 - M160-4

Found - 1967 Brass cap and accessories described by Douglas Co. Surveyor (C.S. file 54/32) **EXCEPT**
10" Cedar @ N.34°E., 25.0 ft, not 14,3 ft. now 12"