



TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

40" dia., fir snag bears S.14½°W., 45.2'  
Unrecorded 13" dia., fir with BLM tag bears N.41°W.,  
15.2'.  
All with healed blaze.  
Set - 6 ft. steel post 2' east.

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #2325, surveyed July/Nov. 2010 - (DCSO records Vol. 57 Page(s) 22756-7)

-----  
The cor. of secs. 25, 26, 35, & 36, perpetuated by Owen, in 1958, from original evidence no longer in existence, remonumented by the Douglas Co. Surveyor's Office, in 1967, and utilized by Riley, in 1990, and by Edwards, in 2009; monumented with an iron post, 1½" dia. firmly set, projecting 14" above the ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Owen  
A fir, 34" dia., bears N.72¼°E., 45.8 ft., with a healed blaze.  
A fir, 41" dia., bears S.70½°E., 67.6 ft., with a healed blaze.  
A fir snag, 43" dia., bears S.14½°W., 46.6 ft., with illegible scribe marks visible on partially healed blaze.  
A fir, 14" dia., bears N.43½°W., 14.7 ft., with a healed double blaze.  
and a new bearing tree  
A fir, 11" dia., bears S.31½°W., 20.4 ft., mkd. T31S R9W S35 BT.  
The iron rod, set by Owen, 1/2" dia., firmly set, projecting 6" above the ground, is alongside the iron post. The steel fence post, set by Edwards, firmly set, projecting 4 ft. above the ground, is E., 2.0 ft. of the iron post.