

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8184)

Set a fir post, 4 ft. long, 4" sq., 24" in the ground, marked S24 on E and S23 ¼ S on W, for the ¼ sec. cor. from which
A fir, 12" dia., bears S.60°E., 25 lks., mkd: S24 ¼ S BT.
A fir, 14" dia., bears S.60°W., 12 lks., mkd: S23 ¼ S BT.

T.H. Mehl, III - For: Robert Dollar Co. - Oct. 12, 1966 - C.S. File 55/15-1

Found - 20" D.Fir BT, S.60°E., 16.5 ft. good condition.
14 D.Fir BT. S.60°W., 7.9 ft., destroyed in clear cut operation.
For the corner, I set a 1½"x30" IP 28" the ground.
Referenced for Sec. 23 -
10" D.Fir, N.4°W. 15.3 ft., scribed "¼ S RS 749 BT"
Bearing Tree was referenced with staff compass & chain, Mag, Var. 19½° E.