TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8186)

Set a basalt stone 16x10x4", 12" in the ground mkd. ¼ on W face for the ¼ sec. cor. from which
A fir, 10" dia., bears N.72°W., 15 lks., mkd: S13 ¼ S BT.
A fir, 16" dia., bears S.80°W., 50 lks., mkd: S 14 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Feb. & March 1967 - C.S. File 54/32-12

Found - Corner stone mkd. "¼" at the corner point.
16" Fir Stump S.80°W., 33.0 ft. scribing "¼" NE Fir gone.
Set - Brass Cap at Cor. mkd. County Surveyors Office, 1967 T31S R9W ¼ S14|S 13
New BTs- 10" D.Fir N.8°W., 28.8 ft. mkd. ¼ S14 CS BT.
30" D.Fir S.25°E., 6.3 ft. mkd. ¼ S13 CS BT.

Fd. Ok by T. Hostetter, 9/2009 - M160-4
Fd. by C. Woodruff, 7/2010 - M161-7