TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8186-7)

Set yew post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 11, 12, 13, & 14, marked T31S S 12 on NE, R9W S 13 on SE, S 14 on SW, S 11 on NW faces, also 4 notches on S & 1 notch on E edges; from which

A fir, 24" dia. bears N.45°E. 59 lks. mkd: T31S R9W S12 BT
A cedar, 36" dia., bears S.35°E., 45 lks., mkd: T31S R9W S13 BT.
A cedar, 36" dia., bears S.50°W., 23 lks., mkd: T31S R9W S14 BT.
A cedar, 16" dia., bears N.12°W., 32 lks., mkd: T31S R9W S11 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Cliff Stone - Feb. 1967 - C.S. File 54/32-2

Found - Orig. Post, scribed S14 S13 R9W.
36", now 52" Cedar, S.50°W. 15.2 ft., opened for scribe "31".
24" Fir, now snag, N.45°E. 38.9 ft., shows good scar
16" Cedar, now burnt stob, N.12°W. 21.1 ft. I find distance to be 24.4 ft.
36" Cedar, now stump S.35°E., 29.7 ft.

Set - Brass Cap at Cor. Mkd: County Surveyors T31S R9W
Office S 11 | S 12
1967 S 14 | S 13

New BTs- 10" D.Fir S.28°E. 21.5 ft. mkd. T31S R9W S13 CS BT.
7" D.Fir N.12°W. 21.3 ft. mkd. T31S R9W S11 CS BT.
6" Laurel N.35°E., 24.2 ft. mkd. T31S R9W S12 CS BT.

Tony Hostetter - For: Roseburg Resources Co. & Plum Creek - Sept. 2009 - M160-4

Found - 1967 Brass cap and accessories described by Douglas Co. Surveyor (C.S. file 54/32) EXCEPT
24" Fir snag @ N.45°E., is now a stump
10" Fir @ S.28°E., is now 18"
7" Fir @ N.12°W., is now 20"
6" Laurel @ N.35°E., is now 9"

Fd. by C. Woodruff, 7/2010 - M161-7