

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8188)

Set a stone 16x10x4", 12" in the ground mkd. ¼ on W side for ¼ sec. cor. from which
A fir, 30" dia., bears N.75°E., 40 lks., mkd: S12 ¼ S BT.
A laurel, 5" dia., bears S.63°W., 7 lks., mkd: S11 ¼ S BT.

Ronald A. Brandt - For: Robert Dollar Co. - July 1971 - C.S. File 55/191

Purpose - To reestablish the obliterated ¼ corner & establish line between those sections. The ¼ corner was monumented and the S½ of the section line brushed out & blazed.

Set - A 1"x36" Iron Rod, driven flush monumenting, from which bears -

A 8.8" D.Fir, N.83°58'W., 19.54 ft., mkd ¼ S11, PE 6803, BT

A 7.2" D.Fir, S.26°46'E, 29.54 ft mkd ¼ S12 PE 6803, BT

Note - Corner set by proportionate measurement. ¼ Cor. post set in 1958 staff compass survey by The Robert Dollar Co. is N.8°W., 2 ft. from the iron rod set in this survey.

Fd. Ok by K. DeGroot, 6/2001 - M137-13