

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec Cor for 1 & 2; 35 & 36, T30-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7381)

Set post cor. secs. 35, 36, 1 and 2, from which
A Fir 50" dia., bears S.50°W., 19 lks. dist.
A Fir 12" dia., bears N.66°W., 105 lks. dist.
A Fir 10" dia., bears S.12°E., 25 lks. dist.
A Laurel 10" dia., bears N.52°E., 40 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Oct. 1964 - C.S. File 53/53-45

Found - 50" now 60" D.Fir stump (orig. BT) S.50°W., 12.5 ft.
shows "31S R9W S2", bark scribe and BT scar.
10" now 24" D.Fir stump (orig. BT) S.12°E., 16.5
ft., shows faint scar.
24" D.Fir N.56°W., 11.8 ft., open and shows "30" in
approx. 60 years.

Set Brass cap at cor. mkd: County Surveyors Office
T30S R9W S 35 | S 36
T31S R9W S 2 | S 1
1964

New BTs- 24" D.Fir N.56°W., 11.8 ft. mkd. T30S R9W S35 CSBT
24" D.Fir, stump, S.12°E., 16.5 ft. mkd. T31S R9W S1
CS BT.
12" W.Fir N.38°E., 19.5 ft. mkd. T30S R9W S36 CS BT.
Corner lies approx. 50 ft. East of new 12 Mile Creek Road.

Fd. OK, DCSO, July 1973 - C.S. File 56/34