

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8182)  
-----  
Set a basalt stone 12x12x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face for the ¼ Sec. cor., from which  
A fir, 4" dia., bears N.10°E., 32 lks., mkd: S25 ¼ S BT.  
A laurel, 6" dia., bears S.6°W., 50 lks., mkd: S36 ¼ S BT.

Reported as not fd. DCSO, John Powell - C.S. File 54/32-20B

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 4/23/2009 - C.S. File 67/28-31  
-----  
Look for not found.  
Found cut line with blazed line searched numerous trees and looked for corner stone. Nothing found.

David Edwards - For: Plum Creek Timberlands - 5/2009 - M159-23  
-----  
Set - 5/8x30" steel rebar w/2½" dia., alum. cap (properly mkd) at proportionate position.  
14" dia., fir bears N.62°E., 21.1 ft.  
17" dia., fir bears N.68°W., 8.92 ft.  
No trees available in sec. 36  
Set 6' steel posts 2' East & 2' West.