

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8185)  
-----  
Set a fir post, 4 ft. long, 4" sq., 24" in the ground, marked S13 ¼ S on N and S24 on S for ¼ sec. cor. from which  
A fir, 36" dia., bears N.50°E., 80 lks., mkd: S13 ¼ S BT.  
A fir, 8" dia., bears S.40°W., 66 lks., mkd: S24 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - March 1967 - C.S. File 54/32-42  
-----  
Found - 36" D.Fir, now stump, N.50°E., 52.8 ft., opened for scribe "T".  
No trace of SW BT  
Set - Brass Cap at Cor. Mkd County Surveyors Office T31S R9W  
1967 ¼ S 13  
S 24  
New BTs- 14" W.Fir S.21½°E., 49.5 ft. mkd. ¼ S24 CS BT.  
12" W.Fir N.70°W., 47.8 ft. mkd. ¼ S13 CS BT.

Corey Woodruff - For: Plum Ck Timberlands - 12/2007 - M155-17  
-----  
Found - BCIP per C.S. 54/32 laying on its side. Reset at distance from fd. DCSO BTs.  
24" W.Fir bears N.62°W., 47.8' (N.70°W., 47.8')  
36" W.Fir bears S.12°E., 49.5' (S.21½°E., 49.5')  
36" D.Fir stump bears N.58°E., 51.7' (N.50°E. 52.8')

Fd. BC & 3 BTs by C. Woodruff - 7/2010 - M161-7