

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 640540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 12

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Kristian DeGroot - For: Roseburg Resources - 6/2001 - M137-13

Set- 5/8"x30" iron rod 29" in the ground w/2" alum. cap
stamped: T31S R9W C¼ • S12 2001 PLS 1941
14" D.Fir bears S.1°27'26"E., 20.8 ft. scribed "C¼
S12 BT"
16" D.Fir bears N.81°52'41"W., 34.0 ft. scribed "C¼
S12 BT"
5/8"x30" iron rod w/plastic cap mkd: "BTS ENG-SURV"
bears S.81°52'41"E., 20.0 ft.
5/8"x30" iron rod w/plastic cap mkd: "BTS ENG-SURV"
bears N.1°27'26"W., 20.0 ft.
Note- All new BTs have double blazed faces w/brass washer
stamped "PLS 1941" nail into the lower blaze.
Bearings are taken to the center of the tree at the
root crown & distances are measured to a nail in the
root crown at the center of the tree all BTs have a
6" red band painted around the tree & the blazed
face painted red & BT signs nailed to the tree.

DCS0-GIS Corner visitation - 1/22/2004 - Typed: 2/10/2011 -
C.S. File 67/33-1

Monument - .625 rebar

Fd. as per M137-13 12/2016 - By R Quimby - C.S. File 65/93-62

Douglas Co. Surveyor's Office - Crew: Stephen J. Flaese and
Jeff Lorsung - 1-9-2025 - C.S. File 67/59-61

Found - 5/8" I.Rod with 2" aluminum cap.
19" D.Fir S.1°27'26"E. 20.8 ft fully healed single
blaze.
23" D.Fir N.81°52'41"W. 34.0 ft fully healed single
blaze.
5/8" I.Rod with plastic cap mkd BTS ENG.- SURV.
S.81°52'41"E. 20.0 ft.
5/8" I.Rod with plastic cap mkd BTS ENG.- SURV.
N.1°27'26"W. 20.0 ft.
Note - Mon is approx 100 ft east of north-south running
gravel road.
Compass decl. 14½°E.