

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8189)

Set a cedar post, 4 ft. long, 4" sq., 24" in the ground, marked S1 ¼S on N and S12 S on S faces, from which
A W.Fir, 16" dia., bears S.63°W., 23 lks. mkd: S12 ¼ S BT.
A cedar, 16" dia., bears N.61°W., 45 lks., mkd: S1 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & E. West - Feb. 1967 - C.S. File 54/32-1

Found - Orig. 16", now 25" Cedar, N.46½°W. 29.7 ft., scribe visible (Record bearing N.61°W.)
Orig. 16", now 29" W.Fir, S.84°W. 15.2 ft., scribe visible. (Record bearing S.63°W.) This tree has been opened, ring count indicates original. Bearing being so far off, I use the two dist. to renew corner.
Set - Brass Cap at Cor. mkd: County Surveyors T31S R9W
Office 1967 ¼ S 1
S 12
New BT - 17" Cedar S.37°W. 13.9 ft. mkd. ¼ S12 CS BT.

Fd. OK by K. DeGroot, 6/2001, M137-13

DCSO-GIS Corner visitation - 1/22/2004 - Typed: 2/10/2011 - C.S. File 67/33-1

Monument - 1½" IP/BC