

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 640640

PRIMARY CORNER DESCRIPTION Center 1/4 cor. Sec. 1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Kristian DeGroot - For: Roseburg Resources - 6/2001 - M137-13

-----  
Set- 5/8"x30" iron rod 29" in the ground w/2" alum. cap  
stamped: T31S R9W C¼ ● S1 2001 PLS 1941  
9" Fir bears N.65°45'E. 25.0 ft. scribed "C¼ S1 BT"  
10" D.Fir bears N.16°01'W., 32.7 ft. scribed "C¼ S1  
BT"  
5/8"x30" iron rod w/plastic cap mkd: "BTS ENG-SURV"  
bears S.65°45'W., 20.0 ft.  
5/8"x30" iron rod w/plastic cap mkd: "BTS ENG-SURV"  
bears S.16°01'E., 20.0 ft.

Note- All new BTs have double blazed faces w/brass washer stamped "PLS 1941" nail into the lower blaze. Bearings are taken to the center of the tree at the root crown & distances are measured to a nail in the root crown at the center of the tree all BTs have a 6" red band painted around the tree & the blazed face painted red & BT signs nailed to the tree.

DCSO-GIS Corner visitation - 2/26/2004 - Typed: 2/10/2011 -  
C.S. File 67/33-1

-----  
Monument - .635                      Comment - ok