

PRIMARY CORNER DESCRIPTION SE. Cor. for Sec. 36

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 19 Page(s) 8103)

-----

I set a Laurel post 4 ft. long, 4" sq., 24" in the ground and mkd. T31S S31 on NE.; R8W S6 on SE.; T32S S1 on SW.; R9W S36 on the NW. faces; also 6 notches on the 4 angles of the same for the cor. to Tps. 31 & 32 S., Rs. 8 & 9 W., from which

- A Fir 40" dia., bears N.36°E., 70 lks. dist. mkd. T31S R8W S31 BT.
- A Fir 10" dia., bears S.45°E., 57 lks. dist. mkd. T32S R8W S6 BT.
- A Fir 40" dia., bears S.66°W., 39 lks. dist. mkd. T32S R9W S1 BT.
- A Fir 30" dia., bears N.23°W., 53 lks. dist. mkd. T31S R9W S36 BT.

GLO resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors, under Special Instructions, Group 35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12186)

-----

Intersect at the cor. of Tps. 31S., Rs. 8 and 9 W., which is a small mound of stone, witnessed as described by the surveyor general, except for a discrepancy in the record of the bearing trees N. of line and that the NE. tree is dead and fallen. I perpetuate this cor., as follows: at the exact cor. point

Set an iron post 3 ft. long, 3" dia., 24" in the ground for cor. of Tps. 31 S., Rs. 8 and 9 W., with brass cap mkd.

T31S	
R9W	R8W
S 36	S 31
1917	

from which

- A Laurel 7" dia., bears N.51°E., 42 lks. dist. mkd. T31S R8W S31 BT. (New BT)
- A Fir 30" dia., bears N.26°W., 52 lks. dist., mkd. T31S R9W S36 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan. 1967 - C.S. File 54/36-78

-----

Found - 30" D.Fir, now stump, N.26°W., 34.3 ft., shows good scar and faint bark scribe "31S".

No trace of NE. Laurel

GLO brass cap marked in 1918.

New BTs- 5" Laurel N.13°W., 26.0 ft. mkd. S36 CS BT.

5" Laurel S.42°E., 21.2 ft. mkd. S1 CS BT.

cont.

PRIMARY CORNER DESCRIPTION SE. Cor. for Sec. 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

David Edwards - For Plum Creek Timberlands - 5/2009 - M159-23

-----  
Found - 1918 GLO brass cap.  
8" dia., Madrone bears S.42°E., 21.2'  
5" dia., dead madrone bears N.13°W., 26.0'  
New BT - 7" dia., fir bears N.32°W., 31.4 ft.  
Set 6 ft. steel post 2' north

BLM Dependent resurvey by Ernest Q. Lundeen, Cadastral Surveyor, under Group No. 2797, surveyed July/Aug 2015 - (DCSO records Vol. 58 Page(s) 23431-2)

-----  
The cor. of T. 31 S., Rs. 8 and 9 W., perpetuated by the Douglas County Surveyor's Office in 1967, as shown on the Douglas County Surveyor's Office corner renewal record in T. 31 S., R. 8 W., point identifier No. 100100, and further perpetuated by Edwards, in 2009; monumented with an iron post, 3" dia., firmly set, projecting 16" above the ground, in a collar of stone, with brass cap (properly) mkd. from which the remains of an original bearing tree  
A sawed and rotted fir stump, 33" dia., bears N.26°W., 34.3 ft., with a healed blaze.  
and BTs mkd. by the Douglas County Surveyor's Office  
A madrone, 9" dia., bears S.43¼°E., 21.4 ft. with no marks visible on rotted, partially healed double blazes.  
A madrone snag, 6" dia bears N.13½°W. 25.2 ft with no marks visible on rotted, partially healed double blazes.  
and a bearing tree mkd. by Edwards  
A fir, 9" dia., bears N.32½°W., 31.4 ft., with a healed blaze.  
and a new bearing tree  
A fir, 5" dia., bears N.20¼°E., 20.9 ft., mkd. X at breast height and BT at the base.  
A steel post set by Edwards, projecting 4.5 ft. above the ground, is North, 2 ft., of the cor.  
Each new bearing tree has a 2½" x ¼" magnetic nail (Mag Nail) driven at the base on right side center.