

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T31-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 19 Page(s) 8104)

-----  
Set a Fir post 4" sq., 4 ft. long, 24" in the ground mkd. T31S R8W S30 on the NE.; S31 on SE.; R9W S36 on SW.; and S25 on the NW. faces; also 1 notch on the S. and 5 notches on the N. angles of same, for the cor. to secs. 25, 30, 31 and 36, and from which

- A Fir 16" dia., bears N.21°E., 90 lks. dist. mkd. T31S R8W S30 BT.
- A Fir 24" dia., bears S.36°E., 80 lks. dist. mkd. T31S R8W S31 BT.
- A Fir 16" dia., bears S.38°W., 13 lks. dist. mkd. T31S R9W S36 BT.
- A Fir 56" dia., bears N.15°W., 58 lks. dist. mkd. T31S R9W S25 BT.

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #727, dated Dec. 20, 1900 - (DCSO records Vol. 19 Page(s) 8239)

-----  
Old corner and witness marks on trees destroyed. Set a stone 16x14x8 ins. at point reestablished by the field notes furnished by the Surveyor General. Remark the old witness trees as indicated by the notes.

BLM Resurvey by C. Albert White, Harold D. Corbing Cadastral Surveyor and Donald R. Beck, Surveying Technician, Under Group #446, Surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 31 Page(s) 13181-82)

-----  
The Sec. Cor., perpetuated with an iron pipe 2" dia., firmly set, 4" above the ground, at record bearing and distance from the remains of the original bearing trees:

- A Fir stump 24" dia., bears N.21°E., 90 lks. dist., with no marks remaining.
- A Fir 50" dia., bears S.36°E., 80 lks. dist., with healed blaze.
- A Fir 33" dia., bears S.38°W., 13 lks. dist., with a healed blaze.
- A Fir 62" dia., bears N.15°W., 58 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: (Cont. Next Page)

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T31-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>T 31 S R 9 W R 8 W <u>S 25   S 30</u> <u>S 36   S 31</u> 1960</p>
<p>from which a new bearing tree A Fir 10" dia., bears N.73°E., 58 lks. dist., mkd. T31S R8W S30 BT. Deposit local cor. marker alongside iron post.</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 4/27/2009 - C.S. File 67/28-30 ----- Found - Stone broken in two out of ground, possible 1900 stone. 1960 BLM BC/IP and 2" IP that BLM fd. now gone. 16" now 24" dia., 2 ft. high rotted D.Fir stump bears N.21°E. 58.6 ft (rec. N.21°E. 59.4 ft) OBT 24" now 50" dia., 6 ft. tall D.Fir, metal cap stump with healed blaze no bark scribing visible bears S.34½°E., 52.8 ft. (Rec. S.36°E., 52.8 ft) OBT 16" now 36" dia., D.Fir bark scribing visible "BT" bears S.38°W., 11.9 ft. rec. S.38°W., 8.6 ft. OBT 56" now 62" dia., 5 ft. tall D.Fir, metal cap stump with illegible bark scribing bears N.13½°W., 38.3 ft. (rec. N.15°W., 38.3 ft) OBT. 10" now 24" dia., W.Fir with a fully healed single blaze, bears N.73°E., 38.3 ft (agrees w/rec) 1960 New - 2½" brass cap on a 1½" dia., by 32" long iron pipe is set at a position determined by 1960 BLM BT &amp; best fit of OBTs. This position is the most likely corner position fd. &amp; perpetuated by 1960 BLM, BC/IP protrudes 7" out of ground. Stones placed along north edge. Compass decl. 16½°E.</p>
<p>Fd. Ok by David Edwards, 5/2009 - M159-23</p>
<p style="text-align: right;">2</p>