

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & 19, T31-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 19 Page(s) 8105)

Set a Laurel post 3 ft. long, 3" dia., 20" in the ground, mkd. ¼ S on the W. side for the ¼ sec. cor., from which
A Fir 14" dia., bears N.71°E., 72 lks. dist. mkd. ¼ S BT
A Laurel 4" dia., bears S.50°W., 8 lks. dist. mkd. ¼ S BT

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #727, dated Dec. 20, 1900 - (DCSO records Vol. 19 Page(s) 8240)

Post and one witness tree gone.
Set a Fir post 4 ft. long, 4" sq., 24" in the ground, mkd. S19 on E.; S24 ¼ S on W. faces, for the ¼ sec. corner, from which
A Fir 18" dia., bears N.71°E., 72 lks. dist. (old witness tree), mkd. ¼ S BT.
A Laurel 6" dia., bears S.30°W., 9 lks. dist. mkd. S24 ¼ S BT.

BLM Resurvey by C. Albert White, Harold D. Corbing Cadastral Surveyor and Donald R. Beck, Surveying Technician, Under Group #446, Surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 31 Page(s) 13184)

The ¼ sec. cor., determined at record bearing and distance from the remaining original bearing trees:
A Fir 32" dia., bears N.71°E., 72 lks. dist., illegible scribe marks visible on opened face.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

¼
S 24 | S 19
R 9 W | R 8 W
T 31 S
1962

from which new bearing trees:
A Fir 12" dia., bears N.18¼°E., 11½ lks. dist. mkd. ¼ S19 BT.
A Fir 12" dia., bears N.86½°W., 63 lks. dist., mkd. ¼ S24 BT.

(Cont. Next Page)

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & 19, T31-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Nov. 1992 - C.S. File 64/35-3

Found - 3" dia. 1962 BLM brass cap on 2½" outside dia. I.P., firmly set and protruding 6" above ground.
An Orig. 24" dia. now 34" dia., breast high D.Fir with fully healed double blaze, bears N.71°E., 48.2 ft. (Rec. N.71°E., 47.5 ft., a face measurement.)
12" now 19" dia. breast high D.Fir with fully healed double blaze, bears N.18¼°E., 7.6 ft. (as per rec. 1962)
12" now 17" dia. breast high D.Fir with fully healed double blaze bears N.86½°W., 40.8 ft. (Rec. N.86½°W., 4.6 ft. dist to center of trunk level with cap.) 1962 BT
Both trees have a small upper blaze and a large lower blaze.
New BT - 4" dia. breast high D.Fir scribed "X BT" on a double blaze, bears S.63°W., 16.8 ft.
Monument is near East edge of random border clear cut and is approx. 100 ft. westerly from BLM forest access road in East half of section 19.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 2-6-25 - C.S. File 67/60-1

Found - ¾" 1962 BLM brass cap on 2½" O.D. Iron pipe proj 6" 36" D.Fir N.71°E. 48.2 ft fully healed double blaze
25" D.Fir N.18¼°E. 7.6 ft fully healed single blaze.
23" D.Fir N.86½°W. 40.3 ft (rec 40.8 ft) fully healed single blaze.
13" D.Fir S.63°W. 16.8 ft fully healed double blaze.
Note: All trees have ¾" mag nails added right side center.
O CRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N 10241.289 E 65218.405
Compass decl. 14½°E.