

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8247-48)

Set a basalt stone 14x10x6 ins., 10" in the ground for cor. to secs. 1, 6, 7 and 12, mkd. with 1 notch on N. and 5 notches on S. edges, from which
A Vine Maple 4" dia., bears N.27°E., 25 lks. dist. mkd. T32S R1W S6 BT.
A Cedar 15" dia., bears S.60°W., 10 lks. dist. mkd. T32S R2W S12 BT.
A Fir 65" dia., bears S.35°E., 7 lks. dist. mkd. T32S R1W S7 BT.
A Fir 15" dia., bears N.36°W., 11 lks. dist. mkd. T32S R2W S1 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby & Wm. Stoffel, crew - March 1963 - C.S. File 53/15-11

Found - Stone at corner as recorded.
Orig. 65" now 65" Fir snag, shows good bark scribing
Orig. 15" now 18" Fir N.36°W., 7.3 ft., shows good scar.
Orig. NE. and SW. BTs not found.
Set Brass cap at cor. mkd: County Surveyors Office
T 32 S
S 1 | S 6
R2W S 12 | S 7 R1W
1963
New BTs- 25" Cedar bears N.17°E., 44.0 ft. scribed S6 T32S R1W CS BT.
12" Cedar bears S.57°W., 81.0 ft. scribed S12 T32S R2W CS BT.
5" Fir bears S.86°E., 64.6 ft. scribed S7 CS BT.

Fd. BC & 5 BTs per B. Shaner 10/1970 - RM 2-21

Jonathan B. Drew, II, USFS - Assisted by: Lance Goucher & Andrew Hellman - 5/14/2015 - C.S. File 65/90-27

Found - A 2½" DCSO brass cap on 1½" galvanized iron pipe, projecting 11" above a mound of stone.
No trace found of a (4" vine maple) 1883
No trace found of a (15" cedar) 1883
An indeterminate size fir snag with no marks visible. (S.35°E., 4.6') 1883
A 32" fir with a healed single blaze. (N.36°W., 7.3') 1883 Cont. next pg

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec Cor for 6 & 7; 1 & 12, T32-2

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A 48" double cedar with a healed single blaze, rec.
(N.17°E., 44.0') 1963
A 24" cedar with a healed double blaze, rec.
(S.57°W., 81.0') 1963
A 19" fir with a healed double blaze, rec. (S.86°E.,
64.6') 1963
No new accessories needed.
Corner maintenance/other info - Clear brush from around
monument and to BTs. Tie flagging to monument and
guard posts, paint BT faces & a 6" band at head
height, add new nails to existing BT tags & add
new tags where needed.
Geodetic coordinates -
LAT: N 42° 48' 38.875" LONG: W 122° 52' 23.651"
Ellipsoid height: 2690 ft.
Datum - WGS 84
Source - USGS QUAD map, for navigation to corner.