

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 cor. for Sec. 6; & 1, T32-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8248)

Set a basalt stone 14x10x5 ins., 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W. face, from which
A Cedar 6" dia., bears N.21°E., 3 1/2 lks. dist. mkd. 1/4 S BT.
A Sugar Pine 40" dia., bears N.84°W., 31 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby & Wm. Stoffel, crew - March 1963 - C.S. File 53/15-6

Found - Orig. 6" now 14" Cedar N.21 1/2°E., 2.0 ft. shows good scar.
Orig. 40" now 46" Sugar Pine, snag, shows good scr, N.84°W., 20.1 ft.

Also find stone as recorded.
Set Brass cap at cor. mkd: County Surveyors Office

T 32 S
1/4 S 1 | S 6
R2W R1W
1963

New BT - 6" Cedar bears S.62°W., 56.0 ft. scribed 1/4 S1 CSBT