

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 19

Alias	Description

Glenn Baughman - For: USFS Tiller Land Survey #20 - Dec. 1976
- M56-69

Set - 2½"x30" IP with brass cap stamped T32S R1W C¼ S19 OLS
536 1976.

BTs - 8" D.Fir bears S.28°W., 17.3 ft., scribed C¼ S19 BT.
12" Fir bears N.3°W., 17.4 ft. scribed C¼ S19 BT.

BLM dependent resurvey by Francis J. Simon, Cadastral
Surveyor under Group #2007, surveyed April/June 2002 - (DCSO
records Vol. 54 Page(s) 21252-3)

The center ¼ sec. cor. of sec. 19, established by Baughman,
in 1976, utilized by Hoffine, in 1995, Jackson County
recorded survey No. 14467 (DCSO does not have this map), and
is accepted as the corner; monumented with an iron post, 2½"
dia., firmly set, projecting 4" above the ground, with brass
cap (properly) mkd.

from which remains of bearing trees mkd. by Baughman

A sawed fir stump, 12" dia., bears S.36°W., 19.6 ft., with
illegible scribe marks visible on a partially healed
double blaze.

A sawed fir stump, 15" dia., bears N.19½°W., 18.1 ft. with
a healed double blaze.

and new bearing trees

A fir, 15" dia., bears N.78½°E., 22.1 ft., mkd. C¼ S19 BT.

A W.Fir, 16" dia., bears S.12½°E., 36.9 ft. mkd. C¼ S19 BT

From this point, NGS triangulation station "DREW", bears
N.8°34'31"W., 35,062.33 feet (mean bearing and sea level
distance), monumented with a brass tablet cemented in a
concrete filled tile pipe, mkd. DREW 1993.

The geographic position (NAD 1927) of the center ¼ section
corner of section 19 as determined by a tie to NGS
Triangulation Station "DREW", is as follows:

Latitude: 42°46'28.95"N. Longitude: 122°51'45.49"W.

BLM Dependent retracement by Arthur R. Rambo, Cadastral
Surveyor under Group No. 2500 Admin file No. 1309, surveyed
Aug/Sept 2013 - (DCSO records, Plat 2015-1 T32S R1W and a
copy in Vol. 58 Page(s) 23176)

The center ¼ sec. cor. of sec. 19, monumented with an iron
post, 2½" dia., firmly set, projecting 2" above the ground,
with brass cap (properly) mkd.

from which remains of BTs mkd. by Baughman, PLS in 1976

A sawed cedar stump, 12" dia., bears S.36°W., 19.6 ft.,
with illegible scribe marks visible on partially healed
blaze. (Record, fir) continued next page

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 140340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 15" dia., bears N.19½°W., 18.1 ft.
with healed double blaze.

and bearing trees mkd. by Simon in 2002

A fir, 15" dia., bears N.78½°E., 22.1 ft., with a healed
blaze.

A fir, 19" dia., bears S.12½°E., 36.9 ft., with a healed
blaze.

NAD 1983 (2011)

Latitude 42°46'28.40"N. Longitude 122°51'49.67"W