

PRIMARY CORNER DESCRIPTION ¼ Cor Secs 7 & 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8281)</p> <p>-----</p> <p>Set a fir post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which</p> <p> A fir, 9" dia., bears N.13°E., 15 lks., mkd: ¼ S BT.</p> <p> A sugar pine, 34" dia., bears S.10°W., 15 lks. mkd: ¼ S BT</p>
<p>Douglas Co. Surveyors Office - James W. Byron, Deputy - Mike Darby & WM. Stoffel - March 1963 - C.S. File 53/15-8</p> <p>-----</p> <p>Found - Orig. 34", now 40" Cedar Snag S.10°W. 9.9 ft., shows good scribing, previously opened, Orig. NE BT. not found.</p> <p>Set brass cap at cor. mkd: County Surveyors ¼ S 7 T32S R1W Office, 1963 S 18</p> <p>New BTs- 30" cedar bears S.3°E., 17.5 ft. scribed ¼ S18 CS BT 12" W.Fir bears N.74°W. 51.2 ft. scribed ¼ S7 CS BT</p>
<p>Raymond Wytcherly - For: Boise Cascade Corp. - May 2004 - M144-50</p> <p>-----</p> <p>Found - 1963 County Brass cap, from which County BT's Cedar 37" dia., bears S.1°E., (S.3°W., 17.5 ft.) face healed over. W.Fir 19" dia., (bears N.74°W., 51.2 ft.) face healed over.</p> <p>New BTs- Pine 9" dia., bears S.75°E., 7.91 ft. scribed "¼ S 18 BT" Fir 6" dia., bears N.29°E., 17.56 ft. scribed "¼ S 7 BT"</p>
<p>Jonathan B. Drew, II, USFS - 5/27/2015 - C.S. File 65/90-21</p> <p>-----</p> <p>Found - A 2½" DCSO brass cap on 1¼" galvanized iron pipe, projecting 7" above the ground. No trace found of a (9" fir)1883 A root hole & pine remains with no marks remaining, rec. (S.10°W., 9.9 ft) 1883 & 1963 A 42" cedar with a healed double blaze, rec. (S.3°E., 17.5 ft) 1963, (S.1°E.)2004 A 20" fir with a healed double blaze, rec. (N.74°W., 51.2 FT)1963 & 2004 A 9" Pine with a pitched over partially healed single blaze, rec. (S.75°E., 7.91 ft) 2004 A 6" Fir with scribe visible on a partially healed single blaze, rec. (N.29°E., 17.56 ft) 2004 No new accessories needed. continued next pg</p>

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION ¼ Cor. Secs. 7 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Corner maintenance/other info - clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.

Geodetic coordinates -

LAT: N.42°47'43.825" LONG: W.122°51'48.251"

Ellipsoid height - 2700 ft.

Datum - WGS 84

Source - USGS QUAD map for navigation to corner