

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8284)</p> <p>-----</p> <p>Set a fir post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which</p> <p>    A matherone, 6" dia., bears N.50°E., 10 lks., mkd: ¼ S BT.</p> <p>    A fir, 12" dia., bears S.50°W., 10 lks., mkd: ¼ S BT.</p>
<p>Douglas Co. Surveyors Office - James W. Byron, Deputy - Mike Darby &amp; Wm Stoffel - March 1963 - C.S. File 53/15-9</p> <p>-----</p> <p>Found - Orig. 12", now 16" dead Fir S.50°W., 6.6 ft. shows good scribing "¼S"</p> <p>    Orig. NE BT not found.</p> <p>Set brass cap at cor. mkd: COUNTY SURVEYORS ¼ <math>\frac{S\ 6}{S\ 7}</math> T32S R1W OFFICE 1968</p> <p>New BTs- 14" W.Fir bears N.60°W., 17.2 ft scribed ¼ S6 CS BT.</p> <p>    22" R.Fir bears S.72°W., 12.0 ft scribed ¼ S7 CS BT.</p>
<p>Douglas Co. Surveyors Office - John M. Powell - Frank Jones &amp; W. Penley - July 1968 - C.S. File 54/71-8</p> <p>-----</p> <p>Found - C.S. brass cap, set &amp; marked in 1963</p> <p>    14" W.Fir, now 15" N.60°W., 17.2 ft. scribe visible.</p> <p>    22" R.Fir, now dead, S.72°W., 12.0 ft scribe visible</p> <p>New BT - 9" D.Fir S.53°E., 133.5 ft. mkd: ¼ S7 CS BT.</p>
<p>Raymond Wytcherly - For: Boise Cascade Corp. - May 2004 - M144-50</p> <p>-----</p> <p>Found - 1963 County brass cap from which</p> <p>    A W.Fir stump bears N.60°W., 17.2 ft., face rotted.</p> <p>    A D.Fir snag, 5 ft. high bears S.72°W., 12.0 ft. face healed over.</p> <p>New BTs- A fir 10" dia., bears N.1°28'W., 48.41 ft., scribed "¼ S 6 BT"</p> <p>    A Fir 7" dia., bears N.52°E., 14.24 ft., scribed "¼ S 7 BT"</p> <p>    A Pine 8" dia., bears S.67°W., 24.60 ft., scribed "¼ S 7 BT"</p> <p>    A Pine 9" dia., bears S.20°E., 39.24 ft., scribed "¼ S7 BT"</p>
<p>Jonathan B. Drew, II, USFS - Assisted by: Lance Goucher - 5/12/2015 - C.S. File 65/90-19</p> <p>-----</p> <p>Found - A 2½" DCSO brass cap on 1¼" galvanized iron pipe, projecting 15" above a mound of stone. cont.</p>

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

No trace found of a (6" matherone)1883  
No trace found of a (12" fir)1883  
An indeterminate size rotten fir stump with no marks visible, rec. (N.60°W., 17.2') 1963  
A 16" rotten fir high stump with no marks visible, rec. (S.72°W., 12.0')1963  
A Fir root hole and shell shows healed single blaze, rec. 12" log alongside, (S.53°E., 133.5')1968  
A 15" fir with a healed single blaze, rec. (N.1°28'W., 48.41')2004  
A 11" Fir with a healed single blaze, rec. (N.52°E., 14.24')2004  
A 13" pine with scribe visible on a partially healed single blaze, rec. (S.67°W., 24.6') 2004  
A 13" pine with scribe visible on a partially healed single blaze, rec. (S.20°E., 39.24') 2004  
No new accessories needed.  
Corner maintenance/other info - clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.  
Geodetic coordinates -  
LAT: N42°48'37.55299" LONG: W122°51'50.20728"  
Elipsoid height - 2360.8 ft  
Datum - PER OPUS: NAD\_83(2011)(EPOCH:2010.0000)  
Source - RTK&STATIC GPS observations from OPUS corrected base.