

PRIMARY CORNER DESCRIPTION Sec Cor for 31 & 32 only, T31-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7460)

-----  
Set post cor. secs. 31 and 32, 5 and 6, from which  
A Fir 18" dia., bears S.73°W., 30 lks. dist.  
A Fir 10" dia., bears N.28°E., 59 lks. dist.  
A Cedar 36" dia., bears N.5°W., 20 lks. dist.  
A Cedar 24" dia., bears S.10°E., 69 lks. dist.

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 18 Page(s) 7491-92)

-----  
The old sec. cor. to secs. 31 & 32, which is a decayed post with 3 bearing trees still standing. I destroyed this post and replaced it with a new post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 31 & 32 mkd. T31S R1W on N. face, S32 on E., and S31 on W. faces, with 5 notches on E. and 1 notch on W. faces, from which  
A Cedar 40" dia., bears N.5°W., 20 lks. dist. mkd. T31S R1W S31 BT.  
A Cedar 30" dia., bears S.10°E., 69 lks. dist. mkd. T32S R1W S6 BT.  
A Fir 25" dia., bears S.73°W., 35 lks. dist. mkd. T32S R1W S6 BT.  
I destroyed the marks on the Cedar that bears S.10°E., and mark  
A Fir 15" dia., bears N.37°E., 47 lks. dist. mkd. T31S R1W S32 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7580-81)

-----  
The cor. of secs. 31 and 32, located by reference to original bearing trees. From cor. point  
A Fir 25" dia., bears S.73°W., 35 lks. dist. mkd. T32S R1W S6 BT. (Old BT)  
A Cedar 40" dia., bears N.5°W., 20 lks. dist. mkd. T31S R1W S31 BT. (Old BT)  
Obliterate the marks on the bearing tree referring to sec. 6 and at exact cor point  
Set an iron post 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 31 and 32 only, with brass cap mkd.

(Cont. Next Page)

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 142700

PRIMARY CORNER DESCRIPTION Sec Cor for 31 & 32 only, T31-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>T31S   R1W <u>S31</u>   S32 T32S R1W S 6 1923</p>
<p>from which A Cedar 16" dia., bears N.38°E., 67 lks. dist. mkd. T31S R1W S32 BT. (New BT)</p>
<p>Douglas Co. Surveyors Office - James Byron, Deputy and crew - March 27, 1963 - C.S. File 53/15-7 ----- Found - Brass cap at corner. Orig. 40" now 44" Cedar N.1°W., not N.5°W., 13.2 ft. Orig. N.38°E., 44.2 ft. Cedar BT, now down, shows scribing. New BTs- Rescribed orig. now 48" Cedar, N.1°W., 15.5 ft. scribed "S31 T31S R1W CS BT" 16" W.Fir bears N.38°E., 54.5 ft. scribed "S32 T31S R1W CS BT CS BT"</p>
<p>Bruce Shaner - For: Umpqua National Forest - Oct. 31, 1970 - RM 2-21 ----- Found - Brass cap properly mkd, US GLO. 12" W.Fir bears N.38°E., 51.5 ft. 48" Cedar, down, scribe not visible, bears N.4°W., 16.0 ft. New BT - Marked a 26" D.Fir, bears N.25°W., 89.0 ft.</p>
<p>Ron Quimby - For: Cow Creek - Nov. 2017 - M171-36 ----- Found - 1923 US GLO BCIP 12" now 22" x 15' tall fir snag bears N.38°E., 51.5' healed scribe 48" cedar snag bears N.4°W., 16.0' no visible scribe 26" now 37" D.Fir bears N.25°W., 89.0' Green metal T-Post bears N.15°W., 3.5' New BTs- 12" fir bears S.68°E., 6.3' - scribed "T32S R1W S32 BT" 21" Fir bears N.55°W., 5.2' - scribed "T31S R1W S31 BT" 11" Fir bears N.21°W., 14.0' - scribed "T31S R1W S31 BT"</p>
<p>2</p>