

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8276)

-----  
A point about 300 ft. below top of Umpqua divide and Set a fir post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on W side; from which  
A fir, 35" dia., bears N.80°E., 11 lks., mkd: ¼ S BT.  
A fir, 26" dia., bears N.60°W., 9 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1968 - C.S. File 54/71-38

-----  
Found - Orig. 35", now 37" D.Fir N.80°E., 7.3 ft., bark scribed "¼ S BT"  
Orig. 26" D.Fir, now down, N.60°W., 5.9 ft., found scribe marks.  
Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R1W  
OFFICE 1968 ¼ S 19|S 20  
Reblazed & rescribed -  
37" D.Fir N.80°E., 7.3 ft. mkd: ¼ S20 CS BT.  
New BT - 14" Fir N.89°W., 8.0 ft., mkd: ¼ S19 CS BT.

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #2007, surveyed April/June 2002 - (DCSO records Vol. 54 Page(s) 21254)

-----  
The ¼ sec. cor. of secs. 19 & 20, perpetuated by the Douglas County Surveyor's Office, in 1968, monumented with an iron post, 1½" dia., firmly set, projecting 9" above the ground, with brass cap (properly) mkd.  
from which the remaining original bearing tree  
A fir, 39" dia., bears N.80°E., 9.0 ft., with scribe marks ¼S BT visible on bark, a large X chop, and a healed blaze. (Record, 7.3 ft.)  
and a bearing tree mkd. by the County Surveyor's Office  
A fir, 21" dia., bears N.89°W., 7.3 ft., with a healed double blaze.

BLM Dependent retracement by Arthur R. Rambo, Cadastral Surveyor under Group No. 2500 Admin file No. 1309, surveyed Aug/Sept 2013 - (DCSO records, Plat 2015-1 T32S R1W and a copy in Vol. 58 Page(s) 23176)

-----  
The ¼ sec. cor. of secs. 19 & 20, monumented with an iron post, 1½" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd.  
from which the remaining original bearing tree  
continued next page

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 40" dia., bears N.80°E., 9.0 ft., with scribe marks BT visible on bark scribe and a healed blaze.  
and a BT mkd. by the Douglas County Surveyor's Office in 1968  
A fir, 22" dia., bears N.89°W., 7.3 ft., with a healed double blaze.  
and a new bearing tree  
A fir, 5" dia., bears N.27°E., 18.9 ft., mkd. X at breast height and BT at base.