

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8279)

-----  
A point about 250 ft. above sec. cor. and Set a basalt stone 16x10x6", 11" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

- A fir, 8" dia., bears N.83°E., 17 lks., mkd: ¼ S BT.
- A fir, 4" dia., bears N.52°W., 33 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - 7/19/1968 - C.S. File 54/71-15

-----  
Reported as not found.  
(Rec. 8" & 4" Fir) Area heavily logged. Fd. mound of stone & stake at approx. cor.

Bruce Shaner - For: USFS - Dec. 1980 - M79-68

-----  
Set - Brass cap mkd: "T32S R1W WM ¼ S18 S17 RLS 430 1980"  
BTs - 10" D.Fir, I scribed "¼ S18 BT" bears S.77°W., 17.9 ft.  
8" D.Fir, I scribed "¼ S17 BT" bears S.24°E., 26.0 ft.

Raymond Wytcherly - For: Boise Cascade Corp. - May 2004 - M144-50

-----  
Found - 1980 brass cap per M 79-68 from which  
D.Fir 18" dia., bears (S.24°E., 26.0 ft) face healed over.  
D.Fir 21" dia., bears (S.77°W., 17.9 ft) face healed over.  
New BTs- Cedar 8" dia., bears N.74°E., 25.1 ft., scribed "¼ S 17 BT"  
Cedar 6" dia., bears N.21°W., 8.7 ft., scribed "¼ S 18 BT"  
Maple 7" dia., bears N.74°W., 18.7 ft., scribed "¼ S 18 BT"

Jonathan B. Drew, II, USFS - Assisted by: Jacob Hunt and Andrew Hillman - 5/10/2018 filed 5/14/2020 - C.S. File 65/106-20

-----  
(Condition report only)  
Found - A 2½" iron pipe with a 3" brass cap, projecting 2" above a collar of stone.  
No trace found of a (1883) 8" fir (N.83°E. 11.22 ft)  
No trace found of a (1883) 4" fir (N.52°W. 21.78 ft)  
A 26" fir with a healed double blaze S.77°W., 17.9 ft 1980, 1989, 2004). Continued next page

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 20" Fir with a healed double blaze. (S.24°E., 26.0 ft. 1980, 1989, 2004)

A 9" Cedar with scribe visible on a partially healed single blaze. (N.74°E., 25.1 ft 2004)

A 8" Cedar with scribe visible on a partially healed single blaze. (N.21°W., 8.7 ft 2004)

A 8" Maple with a healed single blaze. (N.74°W., 18.7 ft 2004)

**No new measurements taken**

Guard posts - South 7.5 ft  
North 3.5 ft  
East 2.0 ft

No new accessories added.

Corner maintenance/other info - Clear brush from around monument & to BTs, BT faces & a 6" band at head height painted red. Add new nails to BT tags & add new tags where needed. monument sizes are outside diameter & BT diameters are at breast height.

NFSL lines bear - (1980)N.1°10'18.8"E., 2488.63 ft & (1980)S.1°10'18.8"W., 2488.63 ft

Geodetic coordinates -

Latitude: N.42°47'18.855" Longitude: W.122°51'12.653"

Datum - WGS84