



PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Jonathan B. Drew, II, USFS - Assisted by: Lance Goucher -  
5/13/2015 - C.S. File 65/90-20

-----  
Found - A 2½" DCSO brass cap on 1¼" galvanized iron pipe,  
projecting 11" above a mound of stone.  
A 20" Fir snag bears, N.33°15'E., 4.0 ft, with a  
partially healed single blaze, rec. (N.43°E.,  
4.0') 1883  
No trace found of a (12" fir)1883  
No trace found of a (6" matherone)1883  
A 22" fir stump bears, N.40°15'W., 5.0 ft, with no  
marks visible, rec. (N.45°W., 4.0') 1883  
A 22" fir stump bears, S.27°W., 31.3 ft, with a  
healed single blaze, rec. (S.25°W., 31.2') 1968  
A 10" fir stub bears, S.2°45'E., 17.4 ft, with  
scribe visible on exposed face, rec. (S.3°E.,  
17.5')1968  
An indeterminate size fir stump bears, N.63°W.,  
20.6 ft, with ax work, rec. (N.65°W., 20.6') 1968  
Rotten remains of an indeterminate size fir bears,  
N.69°W., 28.5 ft, rec. (N.66°W. 28.1') 1980  
New - A 11" pine bears, N.22°30'E., 58.1 ft, marked  
"T32SR1WS5" "BT" on double blaze.  
A 9" Pine bears, S.67°E., 40.4 ft, mkd "T32SR1WS8"  
"BT" on a double blaze.  
A 7" Pine S.9°45'W., 20.6 ft, marked "X""BT" on a  
double blaze.  
A 12" Pine bears, N.63°15'W. 38.4 ft mkd "T32SR1WS6"  
"BT" on double blaze  
Corner maintenance/other info - clear brush from around  
monument and to BTs. Tie flagging to monument and  
guard posts, paint BT faces & a 6" band at head  
height, add new nails to existing BT tags & add  
new tags where needed.  
New BTs include a 3/4" brass washer stamped "ORPLS  
#89396" between B&T  
Geodetic coordinates -  
LAT: N.42°48'37.48773" LONG: W.122°51'14.71715"  
Ellipsoid height - 2132.8 ft.  
Datum - PER OPUS: NAD 83(2011) (EPOCH:2010.0000)  
Source - RTK&STATIC GPS observations from OPUS corrected  
base.