

PRIMARY CORNER DESCRIPTION Sec Cor for 5 & 6 only, (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 18 Page(s) 7490-91)

-----  
(At a point 2.50 chs. West of 1/4 Cor. for 32 only, T31-1)  
Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 5 and 6, marked T31S R1W on S. face; S5 on E.; and S6 on W. faces, with 5 notches on E. and 1 notch on W. faces, from which  
A W.Oak 12" dia., bears N.35°E., 68 lks. dist. mkd. T31S R1W S32 BT.  
A Fir 7" dia., bears S.58°W., 78 lks. dist. mkd. T32S R1W S6 BT.  
A W.Oak 6" dia., bears S.23°E., 26 lks. dist. mkd. T32S R1W S5 BT.

Douglas Co. Surveyors Office - James Byron, Deputy and Ray Irving, crew - July 27, 1953 - C.S. File 45/176

-----  
Found - Mound of stone and stake, stone chiseled.  
Blazed and scribed two trees:  
14" W.Fir S.61°W., 93.2 ft. mkd. T32S S6 CS BT.  
10" Red Fir S.16°E., 115.0 ft. mkd. T32S S5 CS BT.  
No other trees available.

Survey by R.M. Thompson - For: John Toumey - Feb, 8, 1960 - C.S. File 51/171

-----  
I find corner as renewed by County in 1952, a stone mound, from which  
14" W.Fir S.61°W., 93.2 ft. (actual 91.6 ft.), down dead.  
I scribe new BTs:  
8" Maple S.1°40'W., 106.9 ft.  
5" W.Oak, North 55.6 ft.  
No other live trees available.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Dec. 15, 1964 - C.S. File 53/15-13

-----  
Found - Corner stone mound.  
8" Maple S.1°40'W., 106.9 ft. mkd. S5 3683 BT.  
5" W.Oak, North 55.6 ft. mkd. 3683 BT.  
Set Iron pipe with brass cap at cor. mkd:  
County Surveyors Office

-----  
S 6 | S 5  
T 32 S R 1 W  
1964

(Cont. Next Page)

