

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8283)

-----  
Set a yew post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which  
A cedar, 10" dia., bears N.80°W., 14 lks., mkd: ¼ S BT.  
A fir, 45" dia., bears S.45°E., 39 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - 8/1968 - C.S. File 54/71-34

-----  
Reported as not found.  
Area cut & burnt. Good calls, but not found.

Bruce Shaner, RLS #430 - For: USFS, Tiller Ranger Dist. - Oct. 1980 - RM 3-37

-----  
Found - 3" square Yew post original corner  
24" Cedar, orig. BT, scribes ¼ visible bears N.80°W., 9.2'  
45" D.Fir stump, orig. BT., bears S.40°E., 25.7 ft. to face, (Record, S.45°E.)  
Set brass cap mkd. T32S R1W W.M. ¼ S5 S8 R.L.S. 430, 1980  
New BTs- 10" D.Fir BT. I scribed "¼ S8 BT" bears S.46°W., 45.4 ft.  
8" D.Fir BT., I scribed "¼ S5 BT" bears N.32°E., 25.4 ft.