

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 242700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, T31-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7460-61)

Set post cor. secs. 32, 33, 4 and 5, from which
A Fir 6" dia., bears S.86°W., 60 lks. dist.
A Fir 6" dia., bears N.88°W., 57 lks. dist.
A Fir 15" dia., bears N.30°E., 42 lks. dist.
A Fir 15" dia., bears S.35°E., 42 lks. dist.

GL0 Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 18 Page(s) 7489-90)

The old sec. cor. to secs. 32 and 33, which is a decayed post with 4 bearing trees still standing. I destroyed this post and replaced it with a basalt stone 16x8x8 ins., 11" in the ground for cor. to secs. 32 and 33, mkd. with 4 notches on E. and 2 notches on W. edges, from which
A Fir 22" dia., bears N.30°E., 42 lks. dist. mkd. T31S R1W S33 BT.
A Fir 21" dia., bears S.35°E., 42 lks. dist. mkd. T32S R1W S4 BT.
A Fir 12" dia., bears S.86°W., 60 lks. dist. mkd. T32S R1W S5 BT.
A Fir 10" dia., bears N.88°W., 57 lks. dist. mkd. T31S R1W S32 BT.
I destroyed the marks on the Fir that bears S.35°E., and remark the remaining 3 trees.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: Jan. 18, 1961 - C.S. File 51/142-2

Determined by O.B.T.s:
30" W.Fir bears N.88°W., 37.6 ft., found scribe and remarked "S32 BT"
16" W.Fir bears S.86°W., 39.6 ft. (OBT)
24" Fir stump, logged, N.30°E., 27.8 ft. (OBT)
At Corner point, Set 1" x 36" Iron pipe, from which
5" Fir bears S.39°W., 15.5 ft. mkd. S5 R1W BT.
5" Fir bears N.41°W., 20.7 ft. mkd. S32 BT.
A fence corner bears North and also West from corner. Road bears North 355.0 ft.

(Cont. Next Page)

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 242700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, T31-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Kurt Weaver, LS #1679 - For: U.S. Forest Service -
Jan. 1980 - M 82-75 A&B and C.S. File 58/216(n)

Found - W.Fir stump 26" dia. bears N.84°56'W., 38.0 ft.
(Rec. n.84°W., 37.6 ft.)
D.Fir stump 24" dia. bears N.34°48'E., 28.7 ft.
(Rec. N.30°E., 27.8 ft.)
D.Fir 11" dia. bears N.40°30'W., 21.1 ft. (Rec.
N.41°W., 20.7 ft.)
W.Fir 16" dia. bears S.87°21'W., 39.7 ft. (Rec.
S.86°W., 39.6 ft.)
D.Fir 10" dia. bears S.40°06'W., 15.2 ft. (Rec.
S.39°W., 15.5 ft.)
Set 2" x 30" galv. Iron pipe with 2½" brass cap.
New BT - D.Fir 11" dia. bears N.27°30'E., 16.6 ft.

Fd. OK, Dec. 1992 by Kaiser - M 116-30

Ron Quimby - For: Cow Creek - Nov. 2017 - M171-36

Found - Brass cap per M82-15
11" now 20" D.Fir bears N.28°E., 16.6' (N.27°30'E.,
16.6') healed scribe
5" now 18" Fir bears S.40°W., 15.2' (S.39°W., 15.5')
healed scribe
12" now 29" Fir bears S.87°W., 39.7' (S.86°W., 60
lks) healed scribe
5" now 20" Fir bears N.41°W., 21.1' (N.41°W., 20.7')
healed scribe
22" now 24"x2' tall fir stump bears N.35°E., 28.7'
(N.30°E., 42 lks) no visible scribe
10" now 26"x6' tall fir stump bears N.85°W., 38.0'
(N.88°W., 57 lks) partial scribe visible

Adam DeGroot - For: USFS - Oct 2019 - M171-69A&B

Found a 2¼" iron post by Weaver, in 1980 per M82-15 A & B,
firmly set and projecting 6" above ground in an 18" diam.
stone mound with a 2½" brass cap properly mkd. per the
record, with BTs per the 2017 survey M 171-36.