

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8270)

-
- A point about 300 ft. below ¼ sec. cor. and set a basalt stone 14x12x6", 10" in the ground for cor. of secs. 8, 9, 16, & 17 mkd with 4 notches on S & E edges, from which
- A sugar pine, 3" dia., bears N.68°E., 28 lks., mkd: T32S R1W S9 BT.
 - A sugar pine, 6" dia., bears S.32°E., 15 lks., mkd: T32S R1W S16 BT.
 - A matherone, 8" dia., bears S.40°W., 33 lks., mkd: T32S R1W S17 BT.
 - A sugar pine, 3" dia., bears N.58°W., 42 lks., mkd: T32S R1W S8 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1968 - C.S. File 54/71-9

-
- Found - Orig. 3" S.Pine, now 10" snag, N.58°W., 27.7 ft. opened tree for scribe . Tree being dangerous, I cut down leaving 6' stump.
- Orig. 6" S.Pine, now down, S.32°E., 9.9 ft., prev. opened, scribe visible.
- No trace of corner stone or NE or SW BTs
- Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R1W
OFFICE S 8 | S 9
1968 S 17 | S 16
- New BTs- 14" D.Fir S.50°E., 20.3 ft. mkd: T32S R1W S16 CS BT.
8" R.Fir east 11.1 ft. mkd: T32S R1W S9 CS BT.
6" Live Oak N.5°W., 10.9 ft. mkd: T32S R1W S8 CS BT.
9" Live Oak S.80°W., 17.8 ft mkd: T32S R1W S17 CS BT

Kurt C. Weaver, LS 1679 - Witnessess: Herb Farber, Reg Harding, & Bill Trempe - Feb. 15, 1979 - C.S. File 58/176-25

-
- Found - 1968 County brass cap being exposed 17" in a mound of stone & leaning northerly.
- A Sugar pine snag 12" bears N.57°20'W., 28.2 ft. (Rec. N.58°W., 27.7 ft.)
 - A D.Fir snag, 18" bears S.47°51'E., 20.1 ft. (Rec. S.50°E., 20.3 ft.)
 - A Live Oak, 9" bears S.80°59'W., 17.3 ft. (Rec. S.80°W., 17.8 ft.)
 - A Live Oak 7" bears N.4°52'W., 10.6 ft. (Rec. N.5°W., 10.9 ft.)
 - A W.Fir 9" bears East 11.0 ft. (Rec. East 11.1 ft.)

continued next page

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

I perpetuate the corner position by taking the following new tree and place a brass washer bearing my registration number in the lower blaze.

A D.Fir 12" marked T32S R1W S9 BT bears N.75°30'E., 98.0 ft.

Jonathan B. Drew, II, USFS - 5/27/2015 - C.S. File 65/90-25

Found - A 2½" DCSO brass cap on 1¼" galvanized iron pipe, projecting 10" above a mound of stone.
No trace found of a (3" S.Pine) 1883
A root hole & rotten remains of pine with no marks visible.
No trace found of a (8" matherone)1883
A root hole & rotten remains of pine with no marks visible. (N.58°W., 27.7') 1883, (N.57°20'W., 28.2') 1979
A 18" fir high stump with scribe visible on a partially healed upper blaze & a healed lower blaze (S.50°E. 20.3') 1968, (S.47°51'E. 20.1') 1979
A 16" fir with a healed double blaze. (East 11.1 ft) 1968, (11.0 ft) 1979
A 7" Oak with scribe visible on a partially healed double blaze. (N.5°W., 10.9') 1968, (N.4°52'W., 10.6')1979
A 11" Oak with scribe visible on a partially healed double blaze. (S.80°W., 17.8') 1968, (S.80°59'W., 17.3')1979
A 21" Fir with a healed double blaze. (N.75°30'E., 98.0 ft) 1979

No new accessories needed.

Corner maintenance/other info - clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT Tags & add new tags where needed.

Geodetic coordinates -

LAT: N.42°47'42.215" LONG: W.122°50'01.508"

Ellipsoid height: 3120 ft

Datum - WGS 84

Source - Cell phone gps, for navigation to corner.