

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8271)

A point about 200 ft. above ravine & set a basalt stone 12x10x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

- A fir, 12" dia., bears N.50°E., 4 lks., mkd: ¼ S BT.
- A fir, 26" dia., bears West, 7 lks., mkd: ¼ S BT

Douglas Co. Surveyors Office - Frank Jones & W. Penley - Aug. 1, 1968 - C.S. File 54/71-18

Found - Corner stone mkd: "¼"
12" fir, now 11' snag, N.50°E., 2.6 ft. showed scribe "BT". Opened the upper face & found "¼S". Tried to get a ring count but rings are too small. Estimate to be right age.

26" fir now a low stump, West 4.6 ft. shows no face.
Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R1W
OFFICE 1968 ¼ S 8 | S 9

New BTs- 12" D.Fir S.54°W., 35.1 ft. mkd: "¼ S9 CS BT"
26" D.Fir N.82°E., 35.5 ft. mkd: "¼ S8 CS BT"

Note - This corner lies along a N-S cutting line.

Loyd R. Moffit - For: USFS - Nov. 1986 - C.S. File 62/30-22

Found - 1968 County 2½" brass cap on 1" I.P. in rock mound. Fir snag (down) which bears N.50°E., 3.1 ft. (Rec. 2.6 ft) (orig.)
28" Fir which bears N.81°E., 35.8 ft. Scar visible.
Fir stump which bears S.54°W., 35.1 ft.
Fir stump which bears S.89°W., 6.6 ft. (Rec. 4.6 ft.) (Orig.)

New BT - 28" Fir which bears N.37°W., 3.1 ft. scribed ¼ S8 BT with LS washer No. 944 nailed to BT scribe.