

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Pages 8271-2)

A point about 300 ft. above last ravine and Set a fir post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 4, 5, 8, & 9, marked T32S S 4 on NE, R1W S 9 on SE, S 8 on SW, and S 5 on NW faces, with 5 notches on S & 4 notches on E edges; from which

- A fir, 20" dia. bears N.58°E., 34 lks. mkd: T32S R1W S4 BT
- A fir, 12" dia. bears S.45°E., 40 lks. mkd: T32S R1W S9 BT
- A fir, 40" dia. bears S.49°W., 27 lks. mkd: T32S R1W S8 BT
- A cedar, 7" dia. bears N.63°W., 14 lks mkd: T32S R1W S5 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July/Aug. 1968 - C.S. File 54/71-16

Found - 40", now 40" D.Fir, S.49°W., 17.8 ft. scribe visible
7", now 9" Cedar, N.63°W., 9.2 ft., shows good scar.
12" Fir, now down, S.45°E., 26.4 ft.
20", now 20" D.Fir, N.61°E., 24.6 ft. (Rec. N.58°E., 22.4), shows good Scar.

Set brass Cap at Cor. Mkd: COUNTY SURVEYORS T32S R1W
Office S 5 | S 4
1968 S 8 | S 9

New BT - 12" Cedar S.18°E. 14.8 ft. mkd. T32S R1W S 9 CS BT.
All other Bearing Trees O.K. and Tagged.