

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8273)

-----  
Set a basalt stone 16x12x6", 11" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A fir, 22" dia., bears N.68°W., 27 lks., mkd: ¼ S BT.

A fir, 20" dia., bears S.56°E., 24 lks., mkd: ¼ S BT.

-----  
Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July/Aug. 1968 - C.S. File 54/71-17

-----  
Found - Stone at corner, approx. size, but no marks.  
22", now 24" D.Fir, N.68°W. 17.8 ft., shows good scar.

20", now 22" D.Fir, S.56°E. 15.8 ft., prev. opened, scribe visible.

Set brass Cap at Cor. mkd: COUNTY SURVEYORS T32S R1W  
Office, 1968 ¼ S 5 | S 4

Note - All Bearing Trees OK and Tagged.

-----  
Jonathan B. Drew, II, USFS - Assisted by: Jacob Hunt and Andrew Hillman - 5/10/2018 filed 5/14/2020 - C.S. File 65/106-19

-----  
(Condition report only)

Found - A 1½" iron pipe with a 2½" brass cap, projecting 12" above the ground. Record corner accessories and record measurements:

A 24" Fir with healed double blaze (N.68°W. 17.82 ft)

A 23" Fir with healed double blaze (S.56°E. 15.84 ft)

No new accessories added.

Corner maintenance/other info: Clear brush from around monument & to BTs, BT faces & a 6" band at head height painted red. Add new nails to BT tags & add new tags where needed. Monument sizes are outside diameter & BT diameters are at breast height.

Note - Line maintained -500 ft north & -500 ft west  
NFSL Lines bear: (1980) S.81°34'27.4"E., 1301.37 ft  
& (1980) N.1°03'17"E., 2534.08 ft

Guard posts: East-4 ft North-2 ft

Geodetic coordinates -

Latitude: N.42°49'03.617" Longitude: W.122°50'04.115"

Datum: WGS84