TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract #475, dated July 3, 1883 - (DCSO records Vol. 19 Page 8269)

Set a cedar post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. mkd: ¼ S on N face, from which:
A fir, 8" dia., bears N.3°E., 25 lks., mkd: ¼ S BT.
A fir, 16" dia., bears S.25°W., 10 lks., mkd: ¼ S BT.

Edward McGinty, Jackson Co. Surveyor - T. Newcomb - R. Romio - Feb. 12, 1987 (Rec'd 9/13/2005 DCSO) - C.S. File 65/54-36

Found - The single remaining original BT, a D.Fir, 39" dia., containing scribed "BT" in opened lower face, as recorded by R.S. Moore, in 1883. From the proceeding original evidence, set a 1x36" galvanized iron pipe, 27" in the ground with a 2½" dia. brass cap mkd: T32S R1W

¼S $\frac{16}{21}$

C.S.
1987

from which, the above described orig. BT bears rec; S.25°W, 6.6 ft to scribed face. Re-measured 6.93 ft. to center of tree at lower blaze.

Mkd. new tree "CS" "BT":
D.Fir, 9" dia., bears N.31°W., 25.05 ft. to center of tree at lower blaze.
Corner lies on 50% East slope and about 140 ft. East of a spur that slopes S.30°E.
Decl. 20°