

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8271)

Set a basalt stone 15x8x8", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which

A fir, 5" dia., bears N.45°E., 15 lks., mkd: 1/4 S BT.

A fir, 4" dia., bears S.2°W., 29 lks., mkd: 1/4 S BT.

Art Boyer - Witnesses: Geo. Hinsdale & Don Smith - July 31, 1952 - C.S. File 41/59

Found the orig. tree, a 4" fir which has not grown since being marked by surveyor, it was properly scribed, the 1/4S was ok the BT was very distinct, but was upside down; the figure 16 was not clear. Found the orig. rock and placed five other rocks the same size as the corner rock in pile around it. From which

A 24" cedar bears N.63°30'E., 21.0 ft. marked 1/4 S9 1581 BT. This corner is 2657.2 ft. from the NW cor. of section 16 (the recorded distance is 2654.52 ft.) it is at the east side of a flat about 100 ft. west of the beginning of a slope up toward the east, the ground at the corner is flat & slopes at about a 7° rise to the south which begins about 200 ft. south. There are old growth trees around this corner that were big when the small wit. was marked

The tree in sec. 9 was entirely gone, it was a 5" tree.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1968 - C.S. File 54/71-33

Found - No trace of corner stone or SW BT.
24" now 26" cedar, N.63 1/2°E., 21.0 ft. scribe visible
"1/4 S9 BT"

South of line, old logging.

Set brass cap at cor. mkd: COUNTY SURVEYORS T32S R1W
OFFICE 1968 1/4 S 9
S 16

New BT - 13" Double maple S.50 1/2°E., 92.5 ft. mkd: 1/4 S16 CS BT
Note - This corner lies about 190' E of small spring branch