

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8272)

Set a basalt stone 14x12x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

- A fir, 30" dia., bears N.25°W., 18 lks., mkd: ¼ S BT.
- A dogwood, 3" dia., bears S.35°E., 14 lks., mkd: ¼ S BT.

John H. Markham, Jr. - Wit: C.G. Meade - For: Stomar Lbr. Co. April 28, 1959 - C.S. file 51/17

As determined by OBT
32" Fir bears N.25°W., 11.9 ft. OBT Fd. scribe.
At corner point set 1½"x30" iron pipe from which
12" Fir bears N.4°E., 35.2 ft. mkd: ¼ S4 BT.
7" Maple bears S.40°W., 26.5 ft. mkd: ¼ 9 BT.
Corner lies just west of Rock Bluff.
Sec. cor. 3, 4, 9, & 10 bears S.80°10'E., approx. 2900 ft.

Kurt C. Weaver, LS 1679 - Witnessess: Herb Farber, Reg Harding, & Bill Trempe - Feb. 15, 1979 - C.S. File 58/176-24

Found - A 1½" iron pipe with a union and elbow, firmly set and exposed 11" in a mound of stone.
A D.Fir 38" bears N.25°50'W., 11.0 ft. (Rec. N.25°W., 11.9 ft.)
A D.Fir, 48" bark scribed ¼ S9 BT bears S.3°40'W., 33.5 ft. (Rec. S.2°W., 33.5 ft.)
A Maple 10" bears S.40°23'W., 27.0 ft. (Rec. S.40°W., 26,5 ft.)
A dead and down D.Fir, 12" bears record N.4°E., 35.2 ft to stump depression.
Set - A 2"x30" Galv. I.P. in the exact position of the found monument, with a 2½" brass cap marked:
T32S R1W ¼ S4 S9 LS 1679 1979.