

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8262)

A point about 300 ft. below sec. cor. and Set a post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S on W side; from which

- A fir, 6" dia., bears N.58°E., 24 lks., mkd: 1/4 S BT.
- A fir, 6" dia., bears N.77°W., 24 lks., mkd: 1/4 S BT.

BLM Dependent resurvey by Hans W Thielsen, under Group #318, surveyed Aug/Sept 1955 - (DCSO records Vol. 28 Pages 12134-5)

The 1/4 sec. cor. of secs. 15 & 16 determined at the record bearing & distance from the remains of the orig. BTs:

- A fir snag, 10" dia., bears N.58°E., 24 lks., with marks 1/4 S uncovered.
- A fir snag, 8" dia., bears N.77°W., 24 lks., with marks 1/4 S BT uncovered.

At the corner point

Set an iron post, 36" long, 1" dia., 30" in the ground, with brass cap marked:

1/4
S 16|S 15
1955

from which new BTs

- A fir, 31" dia., bears S.55 1/2°E., 55 lks., mkd: 1/4 S15 BT.
- A fir, 31" dia., bears N.55 1/2°W., 26 lks., mkd: 1/4 S16 BT.

Kurt C. Weaver, LS1679 - Witnesses: Herb Farber & Reg Harding - Nov. 1978 - C.S. File 58/176-7

- Found - A 1955 GLO brass cap on a 1" IP firmly set.
Orig. BT, a D.Fir snag 8" bears N.76 1/2°W., 16.9 ft. (Rec. N.77°W., 15.8 ft.)
D.Fir stump 33" bears S.55 1/2°E., 36.2 ft. (rec. S.55 1/2°E., 36.3 ft.)
D.Fir 34" bears N.56 1/4°W., 17.9 ft. (Rec. N.55 1/2°W., 17.2')

I perpetuate the corner position by taking the following new tree and place a brass washer bearing my registration No. in the lower blaze:

- A D.fir 22", marked 1/4 S BT bears N.62°E., 23.7 ft.

Gerald Nygren - For: USFS - July 1989 - C.S. File 63/85-31

- Found - 1" iron pipe with 1955 GLO 2 1/2" brass cap extended 7" above ground.
8" D.Fir stump, N.76 1/2°W., 16.9 ft. (N.77°W., 15.8 ft.) 1978 continued next page

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

34" D.Fir stump, N.56¼°W., 17.9 ft (N.55½°W. 17.2 ft)
33" D.Fir stump, S.55½°E. 36.2 ft (S.55½°E. 36.3 ft)
New BTs- 9" D.Fir, N.89°E., 31.7 ft. scribed "¼ S15 BT"
8" W.Fir, S.72°W., 61.1 ft. scribed "¼ S16 BT"
Nailed 1/2" dia. brass washers mkd. "LS 1035" to lower blaze
of new BTs.
Found - 22" D.Fir dead & down, N.62°E. 23.7 ft (vis. scribe)