

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8264)

A point about 150 ft. above creek and Set a basalt stone 14x12x6", 10" in the ground for cor. of secs. 3, 4, 9, & 10 mkd with 5 notches on S & 3 on E edges, from which

- A fir, 6" dia., bears N.60°E., 10 lks. mkd: T32S R1W S3 BT
- A fir, 10" dia. bears S.73°E., 4 lks. mkd: T32S R1W S10 BT
- A fir, 4" dia., bears S.35°W., 5 lks., mkd: T32S R1W S9 BT
- A fir, 10" dia., bears N.50°W., 6 lks. mkd: T32S R1W S4 BT

BLM Dependent resurvey by Hans W Thielsen, under Group #318, surveyed Aug/Sept 1955 - (DCSO records Vol. 28 Page(s) 12137)

The cor. of secs. 3, 4, 9 & 10, determined at record bearing & distance frm the orig. BTs:

- A fir, 10" dia. bears N.60°E., 10 lks marks W S3 uncovered
- A fir, 16" dia., bears S.73°E., 4 lks. marks 10 uncovered.
- A fir, 8" dia., bears S.35°W., 5 lks., marked with a healed blaze.

At the corner point

Set an iron post, 36" long, 2" dia., 30" in the ground, with brass cap marked:

T32S		R1W	
S	4	S	3
S	9	S	10
1955			

from which new BTs

- A fir, 8" dia., bears N.78°E., 45 lks. mkd: T32S R1W S3 BT
- A chinquapin, 8" dia., bears S.35¼°E., 55 lks., mkd: T32S R1W S10 BT.
- A fir, 21" dia. bears S.82¼°W., 95 lks mkd: T32S R1W S9 BT
- A fir, 30" dia. bears N.21°W., 31 lks. mkd: T32S R1W S4 BT

Fd. Ok by DCSO, JMP - 7/1968 - C.S. 54/71-10