

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8266)

Set a basalt stone 18x8x4", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A live Oak, 4" dia., bears N.82°E., 34 lks., mkd: ¼ S BT.

A matherone, 14" dia., bears N.65°W., 4 lks., mkd: ¼ S BT.

Art Boyer - Witnesses: Herb Northcraft & Ted Shattenkirk - Sept. 1949 - C.S. file 40/214

Found orig. Madrone BT, N.65°W., 4.0 ft. and an old decayed Oak, orig. BT which bears N.82°E., 34 ft.; there is a live oak tree growing out of the decayed Oak BT which I scribed

Oak - scribe ¼ S3 BT 1581

12" Oak bear N.76°E., 4.5 ft. scribed ¼ S3 BT 1581

This cor. is on a 48° slope to the West 300 ft. E of creek & 400 ft. approx. N of a road and on edge of second rocky bluff from the west. There is an old USFS tin yellow tag here.

Douglas Co. Surveyors Office - Frank Jones - W. Penley - 8/1968 - C.S. File 54/71-22

Reported as not found.

We found a tag that said, 4½ chs north to ¼ of 4|3. We fd a good blazed line running N & S but no trace of cor. at all. Call fit real good. There is a logged off unit to west of the sec. line.

Glenn Baughman, LS 536 - For: US Forest Service - Oct. 1979 - C.S. File 58/176-11

Found - 24" Madrone, orig. BT with scribe marks "¼" visible on a partially rotted blaze bears N.65°W., 2.6 ft. (Boyer rec. 4.0 ft.)

4" live Oak with scribe marks "¼ S3" visible on an opened blaze bears N.82°E., 15.8 ft. (Boyers record 34.0 ft.)

12" live Oak, with scribe marks "¼ S3 BT 1581" visible on rotted blaze bears N.84°E., 5.0 ft. (Boyers record N.76°E., 4.5 ft.)

Set - At the corner point set: a 2"x30" iron pipe, 12" in the ground on solid rock, in a 3 ft dia. mound of stone with a 3" brass cap marked: T32S R1W ¼ S4 S3 1979 PLS 536.