

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8265)

Set a basalt stone 18x12x12", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A dogwood, 6" dia., bears N.48°W., 19 lks., mkd: ¼ S BT.

A maple, 4" dia., bears S.58°E., 19 lks., mkd: ¼ S BT.

Art Boyer - Witnesses: Herb North craft & Ted Shattenkirk - Sept. 1949 - C.S. file 40/214

Found orig. maple BT in Sec. 10 for this cor. It had been recently knocked down and was still alive; cut out the scribe marks which were plain although the tree had grown very little. Set a mound of rocks here and blazed and scribed the following:

18" W.Fir S.70°W., 16.5 ft. scribed ¼S 10 BT 1581.

11" Fir N.40°E., 82' scribed ¼S 3 BT 1581.

This corner is on top of a sloping hill which faces the N & is S 35 ft. from a logging road.

Gerald Nygren - For: USFS - July 1989 - C.S. File 63/85-35

CORNER REPORT ONLY

Found - 1955 GLO 2½" brass cap on 1" iron pipe, extended 4" above stone mound.

24" dia. W.Fir, S.83°W., 68.0 ft. (Rec. 89.1 ft.)
(healed blaze)

22" dia. W.Fir, N.74¼°W., 89.1 ft. (Rec. 68.0 ft.)
(healed blaze)

32" dia. W.Fir, N.40°E., 82.0 ft. (healed blaze)

26" dia. W. fir, S.70°W., 16.5 ft. (vis. scribe)

BT signs & monument signs were placed on all BTs without them and a 6" red band and face blazes were painted on all BTs.