

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION No. 1/4 cor. for Sec. 3 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Arthur Boyer, Surveyor - Wit: Herb Northcraft & Ted Schattenkerk - Sept. 1949 - C.S. File 40/214

-----  
Set this cor. mid distance bet. NW. cor. and NE. cor. of sec. 3, which falls 218.2 ft. westerly from sec. cor. 34-35, T31S R1W. Set a 4" x 4" Oak post in a mound of rocks 18" high for cor. Cor. is on a hillside sloping to the North. Bark blazed and scribed the following trees:

30" Fir which bears S.46°W., 8.0 ft. scribed ¼ S3 BT 1581.  
14" Fir which bears S.48°E., 37.2 ft. scribed ¼ S3 BT 1581

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 1968 - C.S. File 54/71-43

-----  
Found - Mound of stone and stake at corner.  
30" now 24" D.Fir S.46°W., 8.0 ft. bark scribed "¼ S3 1581 BT"

14" now 14" D.Fir S.48°E., 37.2 ft., shows good scar  
Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 1 W

-----  
¼ S 3  
T 32 S  
1968

Reblazed and rescribed:  
24" D.Fir S.46°W., 8.9 ft. mkd. ¼ S3 CS BT.