TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8255)

A point about 300 ft. below top of Umpqua divide & set a fir post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec .cor. mkd: ¼S on W face, from which
A fir, 14" dia., bears N.47°E., 15 lks., mkd: ¼ S BT.
A fir, 6" dia., bears S.30°W., 7 lks., mkd: ¼ S BT.

BLM Dependent resurvey by Hans W Thielsen, under Group #318, surveyed Aug/Sept 1955 - (DCSO records Vol. 28 Page(s) 12130)

Point for the ¼ sec. cor. of secs. 14 & 15, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 36 long, 1" dia., 30" in the ground with brass cap marked: ¼
S 15|S 14
1955
from which
A R.Fir, 30" dia., bears S.44½°E., 74 lks., mkd: ¼ S14 BT.
A W.Fir, 12" dia., bears S.47°W., 97 lks., mkd: ¼ S15 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July/Aug. 1968 - C.S. File 54/71-20

Found - GLO Brass cap firmly in ground, properly mkd in 1955
30" now 32" D.Fir S.28½°E., (Rec. S.44°E.) 48.8 ft., scribe marks visible.
12" now 16" W. Fir S.25°W., (Rec. S.47°W., 64.2 ft., axed face not scribed.
This corner set by proportion, as the types of trees were correct, distance good and brass cap firmly in ground, I put in New Bearing Tree:
New BT - 13" D.Fir S.40°W., 67.5 ft. mkd: "¼ S15 CS BT"

Gerald Nygren - For: USFS - July 1989 - C.S. 63/85-26

Found - 1" iron pipe with 1955 GLO 2½" brass cap flush with ground and properly marked.
28" W.Fir bears S.39½°W. 67.7 ft (healed blaze) 1968
39" D.Fir stump bears S.28½°E., 48.7 ft. 1955
New BT - 7" D.Fir bears N.84°E. 20.5 ft. scribed "¼ S14 BT" with 1/2' dia. brass washer mkd. "LS 1035" nailed to lower blaze.