

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8255)  
-----

A point about 250 ft. below ¼ sec. cor. and set a basalt stone 12x8x6" 8" in the ground for cor. to secs. 10, 11, 14, & 15, mkd. with 4 notches on S and 2 notches on E edges, from which

- A fir, 10" dia. bears N.76°E., 14 lks mkd: T32S R1W S11 BT
- A fir, 4" dia. bears S.66°E., 13 lks. mkd: T32S R1W S14 BT
- A hemlock, 10" dia., bears S.35°W., 20 lks., mkd: T32S R1W S15 BT.
- A hemlock, 4" dia., bears N.75°W., 13 lks., mkd: T32S R1W S10 BT.

BLM Dependent resurvey by Hans W Thielsen, under Group #318, surveyed Aug/Sept 1955 - (DCSO records Vol. 28 Pages 12130-1)  
-----

The cor. of secs. 10, 11, 14, & 15, monumented with a weathered basalt stone, 12x8x6" firmly set, with no remaining marks; from which the remains of the orig. NE & SE BTs:

- A stump hole, bears N.76°E., 14 lks.
- A rotted fir stump, bears S.66°E., 13 lks., with no remaining marks.

At the corner point

Set an iron post, 36" long, 2" dia., 30" in the ground, with brass cap marked:

T32S	R1W
<u>S 10</u>	<u>S 11</u>
S 15	S 14
1955	

from which new BTs

- A fir, 20" dia., bears N.83½°E., 80 lks., mkd: T32S R1W S11 BT.
  - A hemlock, 24" dia., bears S.41°E., 53 lks., mkd: T32S R1W S14 BT.
  - A hemlock, 12" dia., bears S.74½°W., 97 lks., mkd: T32S R1W S15 BT.
  - A fir, 16" dia. bears N.4½°W., 81 lks mkd: T32S R1W S10 BT
- Deposit basalt stone alongside the iron post.

Kurt C Weaver, LS #1679 - Witnessess: Herb Farber & Reg Harding - Nov. 1978 - C.S. File 58/176-4  
-----

Found - 1955 GLO brass cap on a 2" IP firmly set.

A dead & down hemlock with scribe visible, the root depression of which bears record N.4½°W., 53.5 ft

A D.Fir 24" with healed blaze bears N.83½°E., 51.7 ft. (Rec. N.83½°E., 52.8 ft)

continued next page

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A hemlock, dead & standing with unhealed blaze & scribe visible bears S.41°E., 33.7 ft. (Rec. S.41°E. 35 ft.)

A hemlock, dead & standing with scribe visible in unhealed blaze bears S.74½°W., 63.7 ft. (Rec. S.74½°W., 64 ft.)

I perpetuate the corner position by taking the following new BT & place a brass washer bearing my registration No. in the lower blaze.

A D.Fir 6" marked "T32S R1W S10 BT" bears N.30°W., 8.6 ft.

A hemlock 6" marked "T32S R1W S14 BT" bears S.17½°E., 12.3 ft.

A D.Fir 6" marked "T32S R1W S15 BT" bears S.38½°W., 20.9 ft.