

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only, (North)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 18 Page(s) 7485)

 (A point 3.00 chs. W. of ¼ sec. cor. S.35)
 Set a Fir post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 2 and 3 mkd. T32S R1W on S. face; S2 on E. and S3 on W. faces, with 2 notches on E. and 4 notches on W. face, from which

- A Matherone 12" dia., bears S.32°E., 44 lks. dist. mkd. T32S R1W S2 BT.
- A Fir 20" dia., bears S.45°W., 11 lks. dist. mkd. T32S R1W S3 BT.
- A Fir 6" dia., bears N.5°W., 29 lks. dist. mkd. T31S R1W S35 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7517-18)

 The cor. of secs. 2 and 3 only, which is a decayed Fir post with marks almost obliterated; from which

- A Fir 20" dia., bears S.45°W., 11 lks. dist. mkd. T32S R1W S3 BT. (Old BT)
- A Fir 6" dia., bears N.5°W., 29 lks. dist. mkd. T31S R1W S35 BT. (Old BT)

The bearing tree in sec. 2 is dead and fallen. I obliterate the marks on the bearing tree referring to sec. 35, and in place of the decayed Fir post, Set an iron post 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 2 and 3, only with brass cap mkd:

T31S R1W

S35

S3 S2
T32S R1W
1923

from which

- A Fir 12" dia., bears S.55°E., 47 lks. dist. mkd. T32S R1W S2 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 1968 - C.S. File 54/71-42

 Found - GLO brass cap at cor., properly marked.
 20" now 36" D.Fir S.45°W., 7.3 ft., shows scar.
 12" now 14" D.Fir S.55°E., 31.0 ft., shows good scar.
 6" D.Fir now down, N.5°W., 19.1 ft.

(Cont. Next Page)

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only, (North)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

(Old BTs, tagged and OK.)
New BT - 17" D.Fir N.15°E., 50.7 ft. mkd. T31S R1W S35 CS BT.
Cor. lies 187.4 ft. W. of Angle point corner.