

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 503700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only, T31-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7518-19)

Set an Iron post 3 ft. long, 1" dia., 28" in the ground for ¼ sec. cor. of sec. 35 only, with brass cap marked:

¼ S 35
1923

from which

A Maple 10" dia., bears N.42°E., 12 lks. dist. mkd. ¼ S35 BT.

A Fir 14" dia., bears N.72°W., 35 lks. dist. mkd. ¼ S35 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 1968 - C.S. File 54/71-40

Found - GLO brass cap at ¼ cor., properly marked.
10" now 12" Maple N.42°E., 7.9 ft., shows good scar.
14" D.Fir now stob, N.72°W., 23.1 ft., shows good scar.

New BT - 26" D.Fir N.22°W., 20.0 ft. mkd. ¼ S35 CS BT.
Cor. lies 37.0 ft. E. of A.P. cor. and about 10 ft. E. of draw.