

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 542700

PRIMARY CORNER DESCRIPTION A.P. on N. bdy. S. 2, E. of ¼ cor.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 18 Page(s) 7480-81 and 7484)

Set a basalt stone 18x12x6 ins., 12" in the ground for the cor. to secs. 35 and 36, about 500 ft. above ¼ sec. cor., marked with 1 notch on E. and 5 notches on W. edges, from which

A Fir 24" dia., bears n.40°E., 7 lks. dist. mkd. T31S R1W S36 BT.

A Fir 26" dia., bears N.36°W., 46 lks. dist. mkd. T31S R1W S35 BT.

A Fir 30" dia., bears S.23°W., 22 lks. dist. mkd. T32S R1W S2 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7519)

The old cor. of secs. 35 and 36, which is a basalt stone, firmly set, 6x12x6 ins. above ground, marked with 1 notch on E. and 5 notches on W. edge; from which

A Fir 16" dia., bears N.40°E., 7 lks. dist. mkd. T31S R1W S36 BT. (Old BT)

A Fir 24" dia., bears N.36°W., 33 lks. dist. mkd. T31s R1W S35 BT. (Old BT)

The bearing tree referring to sec. 2 is dead.
I now change this cor. to an angle point; obliterate marks on bearing trees and re-mark A.P. Re-mark stone A P on N. face.

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 1968 - C.S. File 54/71-35

Found - 6x12x6 stone marked with notches and AP on N. face.
16" D.Fir, now down, N.40°E., 4.6 ft., scribe visible, "AP BT"
24" now 26" D.Fir N.36°W., 21.8 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 1 W

A P

T 32 S

1968

New BT - 22" D.Fir N.41°E., 19.1 ft. scribed A P CS BT.
Cor. lies 50.5 ft. West of sec. cor. for 35 & 36, T31-1