

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 543700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, T31-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7519)

Set an Iron post 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 35 and 36 only, with brass cap marked:

T31S | R1W
S35 | S36

S 2
T32S R1W
1923

from which

A Fir 28" dia., bears N.72°E., 18 lks. dist. mkd. T31S R1W S36 BT.

A Fir 36" dia., bears N.20°W., 4 lks. dist. mkd. T31S R1W S35 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 1968 - C.S. File 54/71-36

Found - 36" now 39" D.Fir N.20°W., 2.6 ft., shows good scar.
28" now 32" D.Fir N.72°E., 11.9 ft., shows good scar
GLO brass cap at cor., properly marked.

New BT - 25" D.Fir S.60°W., 24.5 ft. mkd. T32S R1W S2 CS BT.
Cor. lies 50.5 ft. East of Angle Point.