

TOWNSHIP 32 RANGE 01 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Rufus S. Moore, Deputy Surveyor, under contract 475 dated July 3, 1883 - (DCSO records Vol. 19 Page(s) 8251)

Set a basalt stone 24x12x8", 18" in the ground for cor. to secs. 1, 11, 12, & 2, 200 ft. above last creek, mkd. with 1 notch on E & 5 notches on S. edges, from which
A Matherone, 12" dia., bears N.80°E., 46 lks., mkd: T32S R1W S1 BT.
A Live Oak, 4" dia., bears S.37°E., 32 lks., mkd: T32S R1W S12 BT.
A Fir, 30" dia. bears S.80°W., 25 lks mkd: T32S R1W S11 BT
A Fir, 40" dia., bears N.8°W., 38 lks. mkd: T32S R1W S2 BT

Gerald V. Nygren, LS 1035 - For: Umpqua Nat'l Forest - Aug. 1980 - M79-53 & C.S. 58/158N

Found - Orig. 30" Fir stump bears S.80°W., 16.5 ft.
Orig. 44" Fir snag bears N.8°W. 25.1 ft.
Orig. madrone stool bears N.80°E., 30 ft.
Orig. live oak stool bears S.37°E., 21 ft.
Set - 2½"x30" alum, pipe with alum, cap mkd: "T32S R1W WM 1, 2, 11, & 12 PLS 1035 1980" exposed 4" above ground set from orig. evidence as noted above.
BTs - 16" D.Fir bears S.48°W., 26.1 ft.
8" D.Fir bears N.30°W., 3.5 ft.
16" D.Fir bears N.34°E., 3.6 ft.
6" Live Oak bears S,7°E., 22.8 ft.
Bearing trees have brass washer stamped "RS 1035" nailed to lower blaze.

Fd. Ok by G. Nygren, 9/1993 - M118-20 & C.S. 63/134